



**Voltage Current Rating: 5 AMP.**  
**Dielectric Withstanding Voltage: 1000V AC**  
 Insulation Resistance: 5000MΩ Min.  
 Temperature Range: -25°C to +85°C

PART NO: B04-1043X14N-02

HOUSING COLOR:  
 1 = BLACK  
 5 = WHITE

4	HOUSING	PBT+30%GF	COLOR: SEE PART NO.	
3	REAR SHELL	STEEL	PLATING: Sn	
2	FRONT SHELL	STEEL	PLATING: Ni	
1	TERMINAL	BRASS	TERMINAL FINISH: FULL GOLD FINISHED 2u"	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

△	2014/07/09	NEW ISSUE	JINGLI
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS		Tolerance	
□:	☒:	.x	±0.50
CRITICAL	MAJOR	.x	±0.30
▽:	▽:	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME: HD.D-SUB 104P 车针公头焊线式 (客户用图)				PART NO. B04-1043X14N-02	
REV: A	UNIT: mm	DRW BY: JINGLI	CHK BY: KING ZHOU	APP BY:	DRAWING NO. B04-021
SCALE: N:1	DATE: 2014/07/09	东莞市林诚塑胶电子有限公司 <a href="http://www.lineconn.com">http://www.lineconn.com</a> TEL: 0769-85181660 85181770			
8	7	6	5	4	3