



Voltage Current Rating: 1.5 AMP.
Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 100MΩ Min.
 Temperature Range: -25°C to +85°C
 PART NO: B19-009311A0-0X
 DIM "A": _____
 1:A=4.0mm Bilingual
 2:A=7.0mm Beta

| ITEM | DESC. | MATERIAL | REMAKS | PART REMAKS |
|------|----------|-----------------------|---|-------------|
| 4 | COVERING | PBT+30%G.F.(UL 94V-0) | COLOR: BLACK | |
| 3 | HOUSING | PBT+30%G.F.(UL 94V-0) | COLOR: BLACK | |
| 2 | SHELL | SPCC | OVER-PLATING: Ni | |
| 1 | TERMINAL | C5191 | CONTACT AREA: G/F SOLDER AREA: Sn UNDER-PLATING: Ni | |

| | | | |
|------|------------|-------------|----------|
| △ | 2018/05/30 | NEW ISSUE | JINGLI |
| SIDE | DATE | DESCRIPTION | APPROVER |

| | |
|-------------------|---------------|
| QUALITY SYMBOLS | Tolerance |
| □: ☒: | x. ±0.50 |
| CRITICAL MAJOR | .x ±0.30 |
| ▽: ▽: | .xx ±0.25 |
| ZERO DEFECT S.P.C | |

| | | | | | | | | |
|------------------------|-------------------------------------|-------|------------|-------------------------|-----------|----------------------------|-------------|--|
| NAME: | 1394B 9P MALE SOLDER 四件式 胶护套 (客户用图) | | | | PART NO. | B19-009311A0-0X | | |
| REV: | A | UNIT: | mm | DRW BY | CHK BY | APP BY | DRAWING NO. | |
| SCALE: | N:1 | DATE: | 2018/05/30 | JINGLI | KING ZHOU | | B19-003 | |
| lineconn 东莞市林诚塑胶电子有限公司 | | | | http://www.lineconn.com | | TEL:0769-85181660 85181770 | | |