

PART NO.: B03-0143X1X2-X1

COLOR:




- 1:BLACK
- C:BEIGE

CONTACT AREA:

- A:G/F
- E: Au 5u"
- H: Au 15u"




HOOD OD DIM"A":

- A:6.7mm
- B:7.7mm
- C:8.7mm



ELECTRICAL CHARACTERISTICS


- Contact Current Rating: 1 Amp
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance: 500MΩ/Min
- Contact Resistance: 35mΩ/Max
- Operation Temperature: -25°C ~ +85°C



6	SHRAPNEL	SUS	
5	OUTSIDE SHEEL	SPCC (t=0.50mm)	PLATING: Ni
4	HOOD&WRENCH	ABS+G.F.30% (UL 94V-0)	COLOR: SEE P/N
3	HOUSING&COVER	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK
2	SHEEL	SPCC (t=0.50mm)	PLATING: Ni
1	TERMINAL	COPPER ALLOY (t=0.25mm)	CONTACT AREA: P/N SOLDER AREA: Sn UNDER-PLATING:
ITEM	DESC.	MATERIAL	REMAKS

△				QUALITY SYMBOLS
△				□: ⊗:
△	2008/07/05新版发行		King Zhou	CRITICAL MAJOR
SIDE	DATE	DESCRIPTION	APPROVER	▽: ▽:
8	7			ZERO DEFECT S.P.C

Tolerance		NAME:		SCSI 14P MALE 焊线塑壳装配式鱼钩弹片 (客户用图)				PART NO.		B03-0143X1X2-X1	
x.	±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.		
.x	±0.50	SCALE:	N:1	DATE:	2008/07/05	DAW NHU	KING ZHOU	B03-024			
.xx	±0.30	Lineconn 东莞市林诚塑胶电子有限公司				http://www.lineconn.com		TEL:0769-85181660 85181770			



Lineconn 东莞市林诚塑胶电子有限公司

http://www.lineconn.com

TEL:0769-85181660 85181770