


RoHS



PIN ASSIGNMENT

P1	SIGNAL	P2
1		1
2		2
3		3
4~97		4~97
98		98
99		99
100		100
Shell		Shell

NOTES:

1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
2. CONDUCTOR RESISTANCE: 5 OHMS MAX.
3. INSULATOR RESISTANCE: 1M OHMS MIN, DC 300V 0.01sec.
4. THIS PRODUCT MEET ROHS STANDARD ENVIRONMENTAL PROTECTION POLICY.

ITEM	PART NAME	DESCRIPTION	QY'T
2	CABLE	UL20276 (25P*28#+Mylar))+ 25P*28#+Foamed PP Tape AL.MYLAR+Drain+Braid PVC JACKET COLOR:BLACK OD= 11.5mm	1PCS
1	CONNECTOR	HPDB SCSI 100Pin Male ASS'Y TYPE	2SET

△			
△			
△	2015/05/13	新版发行	Jack Chen
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS		Tolerance		NAME:		SCSI II 100P CABLE ASSEMBLY SCREW (客户用图)		PART NO.		A09-10011XXX-02	
□:	☒:	尺寸(MM)	公差(MM)	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
CRITICAL	MAJOR	300~2000	±50	SCALE:	NONE	DATE:	2015/05/13	Jing Li	Jack Chen		A09-002
▽:	▽:	2001~5000	±100	东莞市林诚塑胶电子有限公司 http://www.lineconn.com TEL:0769-85181660 85181770							
ZERO DEFECT	S.P.C	5001~	±150								

Lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
 TEL:0769-85181660 85181770