



• ELECTRICAL CHARACTERISTICS
 Contact Current Rating: 1 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 500M Ω /Min
 Contact Resistance: 35m Ω /Max
 Operation Temperature: -55°C ~ +105°C

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
7	HOOD	PBT+30%GF	COLOR:BLACK	
6	SCERW	STEEL	PLATING:NI	L=33mm
5	CLAMP	STEEL	PLATING:MATTE TIN AND NI	
4	COVER	PBT+30%GF	COLOR:BLACK	
3	HOUSING	PBT+30%GF	COLOR:BLACK	
2	SHELL	SPCC	PLATING:NI	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: Au 3u" SOLDER AREA: G/F UNDER-PLATING: Ni	

SIDE	DATE	DESCRIPTION	APPROVER
△			
△	2017/10/12	变更螺丝长度	HP GUAN
△	2009/06/04	新版发行	King Zhou

QUALITY SYMBOLS
 □: ☒:
 CRITICAL MAJOR
 ∇: ∇:
 ZERO DEFECT S.P.C

Tolerance
 .x ±0.80
 .x ±0.50
 .xx ±0.30

NAME: 3M同等品 SCSTI 20P MALE SOLDER ASSEMBLY (客户用图)
REV: B **UNIT:** mm **DRW BY:** **CHK BY:** **APP BY:** **DRAWING NO.:** B01-012
SCALE: N:1 **DATE:** 2009/06/04 **DAW NHU** **KING ZHOU**

PART NO.: B01-02031134-01
REMARKS: **PART REMARKS:**

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
 TEL:0769-85181660 85181770