



- ELECTRICAL CHARACTERISTICS
- Contact Current Rating: 1 Amp
  - Dielectric Withstanding Voltage: 500V AC
  - Insulation Resistance: 500MΩ/Min
  - Contact Resistance: 35mΩ/Max
  - Operation Temperature: -25°C ~ +85°C

7	HOOD	PBT+30%GF	COLOR: BLACK	
6	SCERW	STEEL	PLATING: NI	L=33mm
5	CLAMP	STEEL	PLATING: MATTE TIN AND NI	
4	COVER	PBT+30%GF	COLOR: BLACK	
3	HOUSING	PBT+30%GF	COLOR: BLACK	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: Au 3u" SOLDER AREA: G/F UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

△				
△	2017/10/12	依新开模具变更外壳尺寸, 修正温度参数	HP GUAN	
△	2009/06/11	新版发行	King Zhou	
SIDE	DATE	DESCRIPTION	APPROVER	
8	7	6	5	

QUALITY SYMBOLS

□:      ⊠:      △:      ▽:      ○:      ⊕

ZERO DEFECT    S.P.C

Tolerance

x.	±0.80
.x	±0.50
.xx	±0.30

NAME: 3M同等品 SCSTI 26P MALE SOLDER ASSEMBLY TYPE端子全金 (客户用图)

REV: B    UNIT: mm    DRW BY: DAW NHU    CHK BY: KING ZHOU    APP BY:    DRAWING NO. B01-013

SCALE: N:1    DATE: 2009/06/11

Part No. B01-02631134-01

Lineconn 东莞市林诚塑胶电子有限公司    http://www.lineconn.com

TEL: 0769-85181660 85181770