



ELECTRICAL CHARACTERISTICS

Contact Current Rating: 1 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 500MΩ/Min
 Contact Resistance: 35mΩ/Max
 Operation Temperature: -25°C ~ +85°C

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
7	HOOD	PBT+30%GF	COLOR: BLACK	
6	LATCH	ABS,SUS304	COLOR: BLACK	
5	CLAMP	PBT+30%GF	PLATING: MATTE TIN AND NI	
4	COVER	PBT+30%GF	COLOR: BLACK	
3	HOUSING	PBT+30%GF	COLOR: BLACK	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: Au 3u" SOLDER AREA: G/F UNDER-PLATING: Ni	

△				QUALITY SYMBOLS	Tolerance	NAME:	3M同等品 SCS1 36P MALE SOLDER ASSEMBLY TYPE弹片式端子全金 (客户用图)			PART NO.	B01-03631132-01		
△				□: ☒:	.x ±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
△	2009/06/11	新版发行	King Zhou	CRITICAL MAJOR	.x ±0.50	SCALE:	N:1	DATE:	2009/06/11	JING LI	KING ZHOU		B01-016
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C	.xx ±0.30	lineconn 东莞市林诚塑胶电子有限公司			http://www.lineconn.com TEL:0769-85181660 85181770				
8	7	6	5	4	3	2	1						

△				QUALITY SYMBOLS	Tolerance	NAME:	3M同等品 SCS1 36P MALE SOLDER ASSEMBLY TYPE弹片式端子全金 (客户用图)			PART NO.	B01-03631132-01		
△				□: ☒:	.x ±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
△	2009/06/11	新版发行	King Zhou	CRITICAL MAJOR	.x ±0.50	SCALE:	N:1	DATE:	2009/06/11	JING LI	KING ZHOU		B01-016
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C	.xx ±0.30	lineconn 东莞市林诚塑胶电子有限公司			http://www.lineconn.com TEL:0769-85181660 85181770				
8	7	6	5	4	3	2	1						