



ELECTRICAL CHARACTERISTICS

- Contact Current Rating: 1 Amp
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance: 500MΩ/Min
- Contact Resistance: 35mΩ/Max
- Operation Temperature: -25°C ~ +85°C

7	HOOD	PBT+30%GF	COLOR:BLACK	
6	LATCH	ABS,SUS 304	COLOR:BLACK	
5	CLAMP	STEEL	PLATING:MATTE TIN AND NI	
4	COVER	PBT+30%GF	COLOR:BLACK	
3	HOUSING	PBT+30%GF	COLOR:BLACK	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: Au 3u" SOLDER AREA: G/F UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

△				QUALITY SYMBOLS
△			HP GUAN	□: ✕:
△	2009/06/11	新版发行	King Zhou	CRITICAL MAJOR
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C

Tolerance		NAME:		3M同等品 SCS1 26P MALE SOLDER ASSEMBLY TYPE弹片式端子全金 (客户用图)		PART NO.	B01-02631132-01	
x.	±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY
.x	±0.50	SCALE:	N:1	DATE:	2009/06/11	DAW NHU	KING ZHOU	DRAWING NO. B01-015
.xx	±0.30	Lineconn 东莞市林诚塑胶电子有限公司		http://www.lineconn.com		TEL:0769-85181660 85181770		