


ELECTRICAL CHARACTERISTICS

Contact Current Rating: 1 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 500MΩ/Min
 Contact Resistance: 35mΩ/Max
 Operation Temperature: -55°C ~ +105°C

7	HOOD	PBT+30%GF	COLOR: BLACK	
6	LATCH	ABS,SUS 304	COLOR: BLACK	
5	CLAMP	STEEL	PLATING: MATTE TIN AND NI	
4	COVER	PBT+30%GF	COLOR: BLACK	
3	HOUSING	PBT+30%GF	COLOR: BLACK	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: Au 3u" SOLDER AREA: G/F UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

△				QUALITY SYMBOLS	Tolerance	NAME:	3M同等品 SCSI 20P MALE SOLDER ASSEMBLY TYPE弹片式端子全金 (客户用图)				PART NO.	B01-02031132-01	
△				□: ⊠:	x. ±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
△	2009/06/04	新版发行	King Zhou	CRITICAL MAJOR	.x ±0.50	SCALE:	N:1	DATE:	2009/06/04	DAW NHU	KING ZHOU		B01-014
SIDE	DATE	DESCRIPTION	APPROVER	▽: ▽:	.xx ±0.30	Lineconn 东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL:0769-85181660 85181770			
8	7	6	5	ZERO DEFECT S.P.C		4	3	2	1				



Lineconn 东莞市林诚塑胶电子有限公司
<http://www.lineconn.com>
 TEL:0769-85181660 85181770