



• ELECTRICAL CHARACTERISTICS

- Contact Current Rating: 1 Amp
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance: 500MΩ/Min
- Contact Resistance: 35mΩ/Max
- Operation Temperature: -55°C ~ +105°C

7	HOOD	PBT+30%GF	COLOR: BLACK	
6	SCERW	STEEL	PLATING: NI	L=33.0mm
5	CLAMP	STEEL	PLATING: MATTE TIN AND NI	
4	COVER	PBT+30%GF	COLOR: BLACK	
3	HOUSING	PBT+30%GF	COLOR: BLACK	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: Au 3u" SOLDER AREA: G/F UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

△				QUALITY SYMBOLS
△				□: ⊠:
△	2009/06/04新版发行		King Zhou	CRITICAL MAJOR
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C
8	7	6	5	

Tolerance		NAME: 3M同等品 SCS1 14P MALE SOLDER ASSEMBLY TYPE端子全金 (客户用图)		PART NO. B01-01431134-01	
x.	±0.80	REV: A	UNIT: mm	DRW BY DAW NHU	CHK BY KING ZHOU
.x	±0.50	SCALE: N:1	DATE: 2009/06/04		
.xx	±0.30				
				Lineconn 东莞市林诚塑胶电子有限公司 http://www.lineconn.com TEL: 0769-85181660 85181770	
4	3	2	1		