



• ELECTRICAL CHARACTERISTICS

- Contact Current Rating: 1 Amp
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance: 500MΩ/Min
- Contact Resistance: 35mΩ/Max
- Operation Temperature: -25°C ~ +85°C

ITEM	DESC.	MATERIAL	REMARKS
6	SCREW	STAINLESS STEEL	PLANTING Ni 80u-200u"
5	TERMINAL	COPPER ALLOY	CONTACT FINISH OVER-PLATING: Au 30u"(Min.) SOLDER FINISH OVER-PLATING: Au G/F
4	WRENCH SPRING	STAINLESS STEEL	PLANTING Ni 80u-200u"
3	SHELL	SPCC (T=0.50mm)	PLANTING Ni 80u-200u"
2	COVER	ABS	COLOR: BLACK
1	HOUSING	PBT+30%G.F.,UL94V-0	COLOR: BLACK

△				QUALITY SYMBOLS	Tolerance	NAME:	SM 10P MALE SOLDER伺服连接器 (客户用图)				PART NO.	B01-010311A1-01	
△				□: ☒:	x. ±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
△	2016/07/14新版发行		King Zhou	CRITICAL MAJOR	.x ±0.50	SCALE:	N:1	DATE:	2016/07/14	DAW NHU	KING ZHOU		B01-008
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C	.xx ±0.30	lineconn 东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL:0769-85181660 85181770			

