



剖面
A-A

上盖

下盖

ELECTRICAL CHARACTERISTICS

Contact Current Rating: 1 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 500MΩ/Min
 Contact Resistance: 35mΩ/Max
 Operation Temperature: -25°C ~ +105°C

7	HOOD	ABS+30%GF	COLOR: GRAY	
6	SCERW	STAINLESS STEEL		
5	WRENCH SPRING	STAINLESS STEEL		
4	COVER	PBT+30%GF	COLOR: BLACK	
3	HOUSING	PBT+30%GF	COLOR: BLACK	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: Au 3u" SOLDER AREA: G/F UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

△			
△			
△	2013/01/09 新版发行	JACK CHEN	
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS		Tolerance		NAME: PCR-20P伺服连接器 (客户用图)		PART NO. B01-02042134-01	
□:	☒:	x.	±0.80	REV:	A	UNIT:	mm
CRITICAL	MAJOR	.x	±0.50	SCALE:	N:1	DATE:	2013/01/09
▽:	▽:	.xx	±0.30			JING LI	JACK CHEN
ZERO DEFECT	S.P.C			东莞市林诚塑胶电子有限公司		http://www.lineconn.com TEL: 0769-85181660 85181770	
4	3	2	1				