



• ELECTRICAL CHARACTERISTICS

- Contact Current Rating: 1 Amp
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance: 500MΩ/Min
- Contact Resistance: 35mΩ/Max
- Operation Temperature: -25°C ~ +85°C

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
5	LATCH	SUS 304		
4	HOOD	ABS	COLOR: GRAY	
3	HOUSING	LCP+30%GF	COLOR: BLACK	
2	SHELL	SPCC	PLATING: NI	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn UNDER-PLATING: Ni	

				QUALITY SYMBOLS □ : ☒ : CRITICAL MAJOR ▼ : ▼ : ZERO DEFECT S.P.C		Tolerance .x ±0.80 .x ±0.50 .xx ±0.30		NAME: SM 6P MALE SOLDER 伺服连接器 (客户用图)		PART NO. B01-006321A1-02	
				King Zhou		REV: A UNIT: mm DRW BY: DAW NHU		CHK BY: KING ZHOU		APP BY: DRAWING NO. B01-019	
		2016/07/14 新版发行		King Zhou		SCALE: N:1 DATE: 2016/07/14		DAW NHU		KING ZHOU	
SIDE	DATE	DESCRIPTION		APPROVER				lineconn 东莞市林诚塑胶电子有限公司		http://www.lineconn.com TEL: 0769-85181660 85181770	
8	7	6	5	4	3	2	1				