



RoHS



PIN OUT



PART NO.:
 COLOR: A12-0206X XXX-D0
 1: BLACK
 6: BLUE
 LENGTH:
 010:1m
 100:10m

NOTE:
 1. 100% OPEN & SHORT WIRE TEST;
 2. CONTACT RESISTANCE 2ohm Max;
 3. INSULATION RESISTANCE 10M ohm Min;
 4. HI-POT DC 300V;

5	PE	LD-PE		
4	PVC	35P BLUE PVC		
3	CONN. 2	USB3.0 A TYPE 公头 三件套		1PC
2	CONN. 1	USB3.0 IDC 20P 公头 蓝胶		1SET
1	CABLE	UL20276 (USB3.0) (1P#28+DAM)*2C+2C#24+1P#28+ +AEB(AL) OD: 5.5MM		/
NO.	MATERIAL	DESCRIPTION	Q'TY	VENDOR

			QUALITY SYMBOLS
			□: ☒:
			CRITICAL MAJOR
△	2017/04/12	FIRST ISSUE	JING LI
SIDE	DATE	DESCRIPTION	APPROVER

Tolerance		NAME: USB 3.0 IDC 20P M TO AM*2				PART NO. A12-0206X XXX-D0	
尺寸(MM)	公差(MM)	REV: A	UNIT: mm	DRW BY: Jing Li	CHK BY: Jack Chen	DRAWING NO. A12-012	
300~2000	±50	SCALE: NONE	DATE: 2017/04/12				
2001~5000	±100	东莞市林诚塑胶电子有限公司 http://www.lineconn.com TEL:0769-85181660 85181770					
5001~	±150						