

- Current Rating: 1 Amp
- Insulation Resistance: 500MΩ/Min
- Withstanding Voltage: 500V AC/Min
- Contact Resistance: 35mΩ Max
- Temperature Range: -25°C ~ +85°C


6	BOARDLOCK	COPPER ALLOY	PLATING: Tin	
5	BRACKET	SPCC	PLATING: Ni	
4	COVER	LCP+30%GF	COLOR: BEIGE	
3	HOUSING	LCP+30%GF	COLOR: BEIGE	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

QUALITY SYMBOLS

- : ☒ :
CRITICAL MAJOR
▽ : ▽ :
ZERO DEFECT S.P.C

Tolerance

- x. ±0.50
.x ±0.30
.xx ±0.25



NAME:

CISCO (1.0mm) 26P FEMALE RIBBON 90° PCB DOUBLE DECK TYPE (客户用图)

REV:

A UNIT: mm DRW BY

SCALE:

N:1 DATE: 2013/03/07 JINGLI

lineconn 东莞市林诚塑胶电子有限公司

PART NO.

B06-052BC1ED-01

CHK BY

KING ZHOU

APP BY

http://www.lineconn.com
TEL: 0769-85181660 85181770

△	2013/03/07	NEW ISSUE	JINGLI
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

DRAWING NO. B06-007