



ELECTRICAL:

- Current Rating: 2 Amp
- Insulation Resistance: 1000MΩ/Min
- Withstanding Voltage: 500V AC/Min
- Contact Resistance: 50mΩ Max
- Temperature Range: -25°C ~ +85°C

3	HOUSING	PBT+30%GF	COLOR:BLACK	
2	SHELL	SPCC	PLATING:Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA:G/F SOLDER AREA:Sn UNDER-PLATING:Ni	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

				QUALITY SYMBOLS	Tolerance	NAME: SDR 26P PITCH 0.8mm MALE SOLDER TYPE (客户用图)				PART NO.	B06-026311AN-A1		
				□: CRITICAL	x: ±0.50	REV:	A	UNIT:	mm	DRW BY:	CHK BY:	APP BY:	
				⊠: MAJOR	.x: ±0.30	SCALE:	N:1	DATE:	2018/11/16	JACK CHEN	KING ZHOU	B06-014	
				▽: ZERO DEFECT	.xx: ±0.25	东莞市林诚塑胶电子有限公司						http://www.lineconn.com TEL:0769-85181660 85181770	
SIDE	DATE	DESCRIPTION	APPROVER										
8	2018/11/16	NEW ISSUE	JACK CHEN										

3	2	1
---	---	---