



- Current Rating: 1 Amp
- Insulation Resistance: 500M $\Omega$ /Min
- Withstanding Voltage: 500V AC/Min
- Contact Resistance: 35m $\Omega$  Max
- Temperature Range: -25°C ~ +85°C

4	BRACKET	STEEL	PLATING: Ni
3	HOUSING	PBT+30%GF	COLOR: BLACK
2	SHELL	SPCC	PLATING: Ni
1	TERMINAL	COPPER ALLOY T=0.3mm	CONTACT AREA: Au 5 $\mu$ " SOLDER AREA: Sn UNDER-PLATING: Ni
ITEM	DESC.	MATERIAL	REMAKS

				QUALITY SYMBOLS		Tolerance		NAME: SCSI 40P FEMALE 180度 DIP (客户用图)				PART NO. B03-040811EB-0L		
				□:      ☒:		x.      ±0.50		REV: A	UNIT: mm	DRW BY	CHK BY	APP BY	DRAWING NO.	
				CRITICAL MAJOR		.x      ±0.30		SCALE: N:1	DATE: 2010/10/14	JINGLI	KING ZHOU		B03-013	
				▽:      ▽:		.xx      ±0.25		lineconn 东莞市林诚塑胶电子有限公司					http://www.lineconn.com	
SIDE		DATE		DESCRIPTION		ZERO DEFECT S.P.C		TEL: 0769-85181660 85181770						

8	7	6	5	4	3	2	1
---	---	---	---	---	---	---	---