


PCB Layout



- Current Rating: 1 Amp
- Insulation Resistance: 500MΩ/Min
- Withstanding Voltage: 500V AC/Min
- Contact Resistance: 35mΩ Max
- Temperature Range: -25°C ~ +85°C

4	COVER	PBT+30%GF	COLOR:BLACK	
3	HOUSING	PBT+30%GF	COLOR:BLACK	
2	SHELL	SPCC	PLATING:Ni	
1	TERMINAL	COPPER ALLOY T=0.3mm	CONTACT AREA:Au 5u" SOLDER AREA:Sn UNDER-PLATING:Ni	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

				QUALITY SYMBOLS	Tolerance	NAME:	SCSI 100P FEMALE 180度 DIP (客户用图)			PART NO.	<b>B03-100811B-0L</b>		
				□:      ☒:	x.      ±0.50	REV:	<b>A</b>	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
				CRITICAL MAJOR	.x      ±0.30	SCALE:	N:1	DATE:	<b>2010/10/11</b>	JINGLI	KING ZHOU		<b>B03-013</b>
				∇:      ∇:	.xx     ±0.25								
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C									
8	2010/10/11	NEW ISSUE	JINGLI										


**lineconn** 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>  
 TEL:0769-85181660 85181770