



Voltage Current Rating: 1 AMP. 30V AC
Dielectric Withstanding Voltage: 500V AC
 Contact Resistance: 35 mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Temperature Range: -20°C to +85°C

PART NO.:

B03-020618X7-01

CONTACT AREA:
 A:G/F
 C:Au 3u"
 H:Au 15u"

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
5	BRACKET	STEEL	PLATING: Ni	
4	COVER	LCP+30%GF	COLOR: BLACK	
3	HOUSING	PBT+30%GF	COLOR: BLACK	
2	SHELL	ZINC ALLOY	PLATING: Ni	
1	TERMINAL	COPPER ALLOY T=0.3mm	CONTACT AREA: SEE NOTE SOLDER AREA: Sn UNDER-PLATING: Ni	

△				QUALITY SYMBOLS	Tolerance	NAME:	SCSI 20P FEMALE 90度DIP 锌合金壳 (客户用图)			PART NO.	B03-020618X7-01		
△				□: ☒:	x. ±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
△	2015/04/09新版发行		King Zhou	CRITICAL MAJOR	.x ±0.50	SCALE:	N:1	DATE:	2015/04/09	DAWN HU	KING ZHOU		B03-002
SIDE	DATE	DESCRIPTION	APPROVER	▽: ▽:	.xx ±0.25	lineconn 东莞市林诚塑胶电子有限公司			http://www.lineconn.com TEL:0769-85181660 85181770				
8	7	6	5	ZERO DEFECT S.P.C		4	3	2	1				