



- Current Rating: 1 Amp
- Insulation Resistance: 500MΩ/Min
- Withstanding Voltage: 500V AC/Min
- Contact Resistance: 35mΩ Max
- Temperature Range: -25°C ~ +85°C

PART NO: B02-0XX411E0-01

No. OF CONTACTS:
 26 = 26P
 36 = 36P
 50 = 50P
 68 = 68P

Dimensions:

No. of contacts:	A	B	C
26	24.00	19.46	9.30
36	30.40	25.80	8.40
50	39.20	34.70	9.30
68	50.70	46.20	9.30

4	COVER	PBT+30%GF	COLOR:BLACK	
3	HOUSING	PBT+30%GF	COLOR:BLACK	
2	SHELL	SPCC	PLATING:Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

				QUALITY SYMBOLS	Tolerance	NAME: SCSTI PIN TYPE FEMALE SOLDER 装配式主体 (客户用图)				PART NO. B02-0XX411E0-01	
				□: CRITICAL	±0.50	REV: A	UNIT: mm	DRW BY: Jack Chen	CHK BY: Dean Fan	APP BY:	DRAWING NO. B02-023
				☒: MAJOR	±0.30	SCALE: N:1	DATE: 2011/07/15	Jack Chen	Dean Fan		
				▽: ZERO DEFECT	±0.25	lineconn 东莞市林诚塑胶电子有限公司					http://www.lineconn.com
				▽: S.P.C		TEL: 0769-85181660 85181770					
SIDE	DATE	DESCRIPTION	APPROVER								