



• ELECTRICAL CHARACTERISTICS

- Contact Current Rating: 1 Amp
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance: 500MΩ/Min
- Contact Resistance: 35mΩ/Max
- Operation Temperature: -25°C ~ +85°C

3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK
2	SHELL	SPCC	PLATING: Ni
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni
ITEM	DESC.	MATERIAL	REMAKS

QUALITY SYMBOLS		Tolerance		NAME: SCSII PIN TYPE 26P MALE 180° DIP (客户用图)				PART NO. B02-026711EN-10	
□:	☒:	.x	±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY
CRITICAL	MAJOR	.x	±0.50	SCALE:	N:1	DATE:	2016/07/19	JACK CHEN	DEAN FAN
▽:	▽:	.xx	±0.30	lineconn 东莞市林诚塑胶电子有限公司				http://www.lineconn.com	
ZERO DEFECT	S.P.C			TEL:0769-85181660 85181770				DRAWING NO. B02-054	

△			
△			
△	2016/07/19 新版发行	King Zhou	
SIDE	DATE	DESCRIPTION	APPROVER