



PCB Layout

• ELECTRICAL CHARACTERISTICS

- Contact Current Rating: 1 Amp
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance: 500MΩ/Min
- Contact Resistance: 35mΩ/Max
- Operaion Temperature: -25°C ~ +85°C

3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK
2	SHELL	SPCC	PLATING: Ni
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni
ITEM	DESC.	MATERIAL	REMAKS

△			
△			
△	2016/07/19 新版发行	King Zhou	
SIDE	DATE	DESCRIPTION	APPROVER

QUALITY SYMBOLS		Tolerance		NAME: SCSI PIN TYPE 36P MALE 180° DIP (客户用图)		PART NO. B02-036711EN-20	
□:	☒:	x. ±0.80	REV: A	UNIT: mm	DRW BY	CHK BY	APP BY
CRITICAL	MAJOR	.x ±0.50	SCALE: N:1	DATE: 2016/07/19	JACK CHEN	DEAN FAN	DRAWING NO. B02-055
▽:	▽:	.xx ±0.30	东莞市林诚塑胶电子有限公司				
ZERO DEFECT	S.P.C			http://www.lineconn.com TEL: 0769-85181660 85181770			