

• ELECTRICAL CHARACTERISTICS

Contact Current Rating: 1 Amp  
 Dielectric Withstanding Voltage: 500V AC  
 Insulation Resistance: 500MΩ/Min  
 Contact Resistance: 35mΩ/Max  
 Operation Temperature: -25°C ~ +85°C


PART NO: B02-050F11E0-X1

PCB MOUNTING:  
 A:1.0mm(For PCB 1.2mm)  
 B:1.4mm(For PCB 1.6mm)

3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR:BLACK
2	SHELL	SPCC	PLATING:Ni
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni
ITEM	DESC.	MATERIAL	REMAKS

△			
△			
△	2016/08/04新版发行	King Zhou	
SIDE	DATE	DESCRIPTION	APPROVER

QUALITY SYMBOLS		Tolerance		NAME:		SCSI PIN TYPE 50P FEMALE夹板组装式 (客户用图)		PART NO.		B02-050F11E0-X1	
□:	☒:	x.	±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
CRITICAL	MAJOR	.x	±0.50	SCALE:	N:1	DATE:	2016/08/04	JACK CHEN	DEAN FAN		B02-060
▽:	▽:	.xx	±0.30	lineconn		东莞市林诚塑胶电子有限公司		http://www.lineconn.com		TEL:0769-85181660 85181770	
ZERO DEFECT	S.P.C										



Tolerance		NAME:		SCSI PIN TYPE 50P FEMALE夹板组装式 (客户用图)		PART NO.		B02-050F11E0-X1	
x.	±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
.x	±0.50	SCALE:	N:1	DATE:	2016/08/04	JACK CHEN	DEAN FAN		B02-060
.xx	±0.30	lineconn		东莞市林诚塑胶电子有限公司		http://www.lineconn.com		TEL:0769-85181660 85181770	