

No. of Contact	A	B	C	D
09	16.9	25.0	30.8	11.1
15	25.2	33.3	39.1	19.4
25	39.0	47.0	53.0	33.2
37	54.4	63.5	69.3	49.9

Voltage Current Rating: 5 AMP.
Dielectric Withstanding Voltage: 1000V AC
 Insulation Resistance: 1000MΩ Min.
 Temperature Range: -25°C to +85°C

PART NO: B05-0XX5X1AD-F5

NO.OF CONTACT:
 09 = 9 pos
 15 = 15 pos
 25 = 25 pos
 37 = 37 pos


HOUSING COLOR:
 1 = BLACK
 5 = WHITE
 6 = BLUE

5	SCREW	STEEL	PALTING: Ni	
4	BOARDLOCK	COPPER ALLOY	PALTING: Ni	
3	HOUSING	PBT+30%GF	COLOR: BLACK	
2	SHELL	SPCC	PALTING: Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

QUALITY SYMBOLS

□: ☒: CRITICAL MAJOR
 ▽: ▽: ZERO DEFECT S.P.C

Tolerance
 .x ±0.50
 .x ±0.30
 .xx ±0.25



NAME:	D-SUB MALE 90度DIP 8.08mm前锁5.8mm螺母 (客户用图)				PART NO.	B05-0XX5X1AD-F5		
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	
SCALE:	N:1	DATE:	2011/03/07	JINGLI	KING ZHOU		B05-084	
lineconn 东莞市林诚塑胶电子有限公司				http://www.lineconn.com		TEL:0769-85181660 85181770		

2011/03/07

NEW ISSUE

JINGLI

SIDE DATE DESCRIPTION APPROVER

8

7

6

5

4

3

2

1