



No. of Contact	A	B	C	D
09	16.9	25.0	30.8	19.0
15	25.3	33.3	39.2	27.7
25	39.0	47.0	53.0	41.0
37	55.4	63.5	69.4	57.3

Voltage Current Rating: 5 AMP.
Dielectric Withstanding Voltage: 1000V AC
 Insulation Resistance: 1000MΩ Min.
 Temperature Range: -25°C to +85°C

PART NO: B05-0XX3X1AN-S4

NO.OF CONTACT:

- 09 = 9 pos
- 15 = 15 pos
- 25 = 25 pos
- 37 = 37 pos

HOUSING COLOR:

- 1 = BLACK
- 5 = WHITE
- 6 = BLUE

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
5	SCREW	STEEL	PALTING: Ni	
4	REAR SHEEL	SPCC	PALTING: Sn	
3	FRONT SHEEL	SPCC	PALTING: Ni	
2	HOUSING	PBT+30%GF	COLOR: SEE PART NO.	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn	

QUALITY SYMBOLS

- : CRITICAL
- ☒: MAJOR
- ▽: ZERO DEFECT
- ▽: S.P.C

Tolerance

- .x ±0.50
- .x ±0.30
- .xx ±0.25

NAME:

D-SUB 公头一体焊线式后铆4.0通孔螺母 (客户用图)

REV: A

UNIT: mm

DRW BY: JINGLI

CHK BY: KING ZHOU

PART NO: B05-0XX3X1AN-S4

SCALE: N:1

DATE: 2020/07/06

JINGLI

KING ZHOU

APP BY: APP BY

DRAWING NO: B05-070



东莞市林诚塑胶电子有限公司

http://www.lineconn.com

TEL: 0769-85181660 85181770

SIDE	DATE	DESCRIPTION	APPROVER
△	2009/05/26	NEW ISSUE	JINGLI