

No. of Contact	A	B	C	D
09	16.3	25.0	30.8	19.0
15	24.8	33.3	39.2	27.7
25	38.3	47.0	53.0	41.0
37	54.8	63.5	69.4	57.3

Voltage Current Rating: 5 AMP.
Dielectric Withstanding Voltage: 1000V AC
 Insulation Resistance: 1000MΩ Min.
 Temperature Range: -25°C to +85°C

PART NO: B05-0XX4X1AN-S4

NO.OF CONTACT:

- 09 = 9 pos
- 15 = 15 pos
- 25 = 25 pos
- 37 = 37 pos

HOUSING COLOR:

- 1 = BLACK
- 5 = WHITE
- 6 = BLUE

5	SCREW	STEEL	PALTING: Ni	
4	REAR SHELL	SPCC	PALTING: Sn	
3	FRONT SHELL	SPCC	PALTING: Ni	
2	HOUSING	PBT+30%GF	COLOR: SEE PART NO.	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

QUALITY SYMBOLS

- : ☒: CRITICAL MAJOR
- ▽: ▽: ZERO DEFECT S.P.C

Tolerance

- .x ±0.50
- .x ±0.30
- .xx ±0.25

NAME:

D-SUB 母头焊线式后铆4.0通孔螺母 (客户用图)

REV: A

UNIT: mm

DRW BY: JINGLI

CHK BY: KING ZHOU

PART NO: B05-0XX4X1AN-S4


SCALE: N:1

DATE: 2010/01/07

JINGLI

KING ZHOU

APP BY: DRAWING NO: B05-071



lineconn 东莞市林诚塑胶电子有限公司

http://www.lineconn.com
 TEL: 0769-85181660 85181770

NEW ISSUE

JINGLI

SIDE DATE DESCRIPTION APPROVER