



No. of Contact	A	B	C	D
15	16.3	25.0	30.8	19.3
26	24.7	33.3	39.1	27.7
44	38.3	47.0	53.0	41.0
62	54.8	63.5	69.3	57.3

Voltage Current Rating: 5 AMP.
Dielectric Withstanding Voltage: 1000V AC
 Insulation Resistance: 1000MΩ Min.
 Temperature Range: -25°C to +85°C

PART NO: B04-0XX4X1A0-E5

NO.OF CONTACT:
 15 = 15 pos
 26 = 26 pos
 44 = 44 pos
 62 = 62 pos

HOUSING COLOR:
 1 = BLACK
 5 = WHITE
 6 = BLUE

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
5	SCREW	STEEL	PALTING: Ni	
4	REAR SHELL	SPCC	PALTING: Sn	
3	FRONT SHELL	SPCC	PALTING: Ni	
2	HOUSING	PBT+30%GF	COLOR: SEE PART NO.	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn	

QUALITY SYMBOLS		Tolerance		NAME: HD.D-SUB 母头焊线式前铆5.8实芯螺母 (客户用图)				PART NO. B04-0XX4X1A0-E5			
□:	☒:	.x	±0.50	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
CRITICAL	MAJOR	.x	±0.30	SCALE:	N:1	DATE:	2010/08/29	JINGLI	KING ZHOU		B04-019
∇:	∇:	.xx	±0.25	东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL: 0769-85181660 85181770			
ZERO DEFECT	S.P.C										

SIDE	DATE	DESCRIPTION	APPROVER
△	2010/08/29	NEW ISSUE	JINGLI