



No. of Contact	A	B	C	D
15	16.3	25.0	30.8	19.0
26	24.8	33.3	39.2	27.7
44	38.3	47.0	53.0	41.0
62	54.8	63.5	69.4	57.3

**Voltage Current Rating: 5 AMP.**  
**Dielectric Withstanding Voltage: 1000V AC**  
 Insulation Resistance: 1000MΩ Min.  
 Temperature Range: -25°C to +85°C

PART NO: B04-0XX4X1A0-SD

NO.OF CONTACT:

- 15 = 15 pos
- 26 = 26 pos
- 44 = 44 pos
- 62 = 62 pos

HOUSING COLOR:

- 1 = BLACK
- 5 = WHITE
- 6 = BLUE

ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS
5	SCREW	STEEL	PALTING: Ni	
4	REAR SHELL	SPCC	PALTING: Sn	
3	FRONT SHELL	SPCC	PALTING: Ni	
2	HOUSING	PBT+30%GF	COLOR: SEE PART NO.	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn	

QUALITY SYMBOLS		Tolerance		NAME: HD.D-SUB 母头 焊线式 后铆 4.0 通孔 螺母 (客户用图)				PART NO. B04-0XX4X1A0-SD	
□:	☒:	x.	±0.50	REV: A	UNIT: mm	DRW BY	CHK BY	APP BY	DRAWING NO.
CRITICAL	MAJOR	.x	±0.30	SCALE: N:1	DATE: 2016/08/11	JINGLI	KING ZHOU		B04-023
∇:	∇:	.xx	±0.25	lineconn 东莞市林诚塑胶电子有限公司				http://www.lineconn.com	
ZERO DEFECT	S.P.C			TEL: 0769-85181660 85181770					

SIDE		DATE		DESCRIPTION		APPROVER	
8		7		6		5	
2016/08/11		NEW ISSUE		JINGLI			