

PCB LAYOUT

High Power Contact Current Rating:
10,20 or 40AMPS
High Power Contact Resistance:
2.7 Milliohms Max.
Dielectric Withstanding Voltage:
1000V AC For 1 Minute
Insulation Resistance:5000MΩ Min.
Temperature Range:-25°C to +85°C

PART NO:

B08-7W26114D-X1

Current Rating:

- A = 10 AMPS Dim.A ϕ 1.7 Dim.B ϕ 2.2
- B = 20 AMPS Dim.A ϕ 2.8 Dim.B ϕ 3.3
- C = 30 AMPS Dim.A ϕ 3.2 Dim.B ϕ 3.7
- D = 40 AMPS Dim.A ϕ 3.7 Dim.B ϕ 4.2

6	JACKSCREWS	BRASS	PLATING:Ni	
5	HOUSING	PBT+30%GF	COLOR: WHITE	
4	RIVETED INSERT	BRASS	PLATING:Ni	
3	REAR SHELL	SPCC	PLATING:Sn	
2	FRONT SHELL	SPCC	PLATING:Ni	
1	TERMINAL	BRASS	TERMINAL FINISH: FULL GOLD FINISHED 2u"	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

QUALITY SYMBOLS

□: ☒:
CRITICAL MAJOR
▽: ▽:
ZERO DEFECTS.P.C

Tolerance

x. ±0.50
.x ±0.30
.xx ±0.25

NAME:

7W2 90度母头铆支架鱼叉锁螺丝 POWER D-SUB (客户用图)

PART NO.

B08-7W26114D-X1

REV:

A

UNIT:

mm

DRW BY

CHK BY

APP BY

DRAWING NO.

SCALE:

N:1

DATE:

2017/05/08

JINGLI

KING ZHOU

B08-038

Lineconn

东莞市林诚塑胶电子有限公司

http://www.lineconn.com

TEL: 0769-85181660 85181770



2017/05/08

NEW ISSUE

JINGLI

SIDE

8

DATE

DESCRIPTION

7

APPROVER

6

QUALITY SYMBOLS

Tolerance

x. ±0.50
.x ±0.30
.xx ±0.25

NAME:

7W2 90度母头铆支架鱼叉锁螺丝 POWER D-SUB (客户用图)

PART NO.

B08-7W26114D-X1

REV:

A

UNIT:

mm

DRW BY

CHK BY

APP BY

DRAWING NO.

SCALE:

N:1

DATE:

2017/05/08

JINGLI

KING ZHOU


B08-038

Lineconn

东莞市林诚塑胶电子有限公司

http://www.lineconn.com

TEL: 0769-85181660 85181770



4

3

2

1