

PCB LAYOUT

High Power Contact Current Rating:  
10,20 or 40AMPS  
High Power Contact Resistance:  
2.7 Milliohms Max.  
Dielectric Withstanding Voltage:  
1000V AC For 1 Minute  
Insulation Resistance:5000MΩ Min.  
Temperature Range:-25°C to +85°C

PART NO:  
B08-8W85X14D-X1

HOUSING COLOR:  
1:BLACK  
3:GREEN  
5:WHITE

CURRENT RATING:  
A = 10 AMPS Dim.A  $\phi 1.7$  Dim.B  $\phi 2.2$   
B = 20 AMPS Dim.A  $\phi 2.8$  Dim.B  $\phi 3.3$   
C = 30 AMPS Dim.A  $\phi 3.2$  Dim.B  $\phi 3.7$   
D = 40 AMPS Dim.A  $\phi 3.7$  Dim.B  $\phi 4.2$


ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS
6	JACKSCREWS	BRASS	PLATING:Ni	
5	HOUSING	PBT+30%GF	COLOR:SEE PART NO.	
4	RIVETED INSERT	BRASS	PLATING:Ni	
3	REAR SHELL	SPCC	PLATING:Sn	
2	FRONT SHELL	SPCC	PLATING:Ni	
1	TERMINAL	BRASS	TERMINAL FINISH:FULL GOLD FINISHED 2u"	

QUALITY SYMBOLS

□:      ☒:  
CRITICAL MAJOR  
▽:      ▽:  
ZERO DEFECTS.P.C

Tolerance

.x      ±0.50  
.x      ±0.30  
.xx     ±0.25



NAME:

8W8 90度公头铆支架鱼叉锁螺丝 POWER D-SUB (客户用图)

REV:

A

SCALE:

N:1

UNIT:

mm

DATE:

2017/05/08

DRW BY:

JINGLI

CHK BY:

KING ZHOU

PART NO.

B08-8W85114D-X1

APP BY:

DRAWING NO.

B08-039

http://www.lineconn.com

TEL:0769-85181660 85181770

lineconn 东莞市林诚塑胶电子有限公司



2017/05/08

NEW ISSUE

JINGLI

SIDE

8

DESCRIPTION

7

APPROVER

6

QUALITY SYMBOLS

5

Tolerance

4

NAME:

3

REV:

2

SCALE:

1

DRW BY:

JINGLI

CHK BY:

KING ZHOU

APP BY:

DRAWING NO.

B08-039

http://www.lineconn.com

TEL:0769-85181660 85181770

lineconn 东莞市林诚塑胶电子有限公司