



ELECTRICAL CHARACTERISTICS

Contact Current Rating: 1 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 500MΩ/Min
 Contact Resistance: 35mΩ/Max
 Operation Temperature: -25°C ~ +85°C

ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS
7	HOOD	PBT+30%GF	COLOR:BLACK	
6	LATCH	ABS,SUS 304	COLOR:BLACK	
5	CLAMP	STEEL	PLATING:MATTE TIN AND NI	
4	COVER	PBT+30%GF	COLOR:BLACK	
3	HOUSING	PBT+30%GF	COLOR:BLACK	
2	SHELL	SPCC	PLATING:Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: Au 3u" SOLDER AREA: G/F UNDER-PLATING: Ni	

A		B		C		D		E		F	
△											
△											
△	2009/06/11 新版发行		King Zhou	QUALITY SYMBOLS	Tolerance	NAME:	3M同等品 SCSTI 50P MALE SOLDER ASSEMBLY TYPE弹片式 端子全金 (客户用图)		PART NO.	B01-05031132-01	
SIDE	DATE	DESCRIPTION	APPROVER	CRITICAL MAJOR	x. ±0.80 .x ±0.50 .xx ±0.25	REV: A	UNIT: mm	DRW BY: JING LI	CHK BY: KING ZHOU	APP BY:	DRAWING NO. B01-017
8	7	6	5	ZERO DEFECT S.P.C		SCALE: N:1	DATE: 2009/06/11	JING LI	KING ZHOU		
						Lineconn 东莞市林诚塑胶电子有限公司		http://www.lineconn.com			
								TEL:0769-85181660 85181770			