



NO. of CONTACTS	A	B	C	D	E	F	G
20	33.38	27.45	16.44	20.83	11.43	22.3	27.45
26	37.19	31.26	20.25	24.64	15.24	26.13	31.26
36	43.54	37.61	26.60	30.99	21.59	32.48	37.61

• PART NO.:

B03-0XX011EB-02

No. of:

20:20P

26:26P

36:36P

**Voltage Current Rating: 1AMP**  
**Dielectric Withstanding Voltage: 500V AC**  
 Contact Resistance: 35 mΩ Max.  
 Insulation Resistance: 500MΩ Min.  
 Temperature Range: -20°C to +85°C

3	HOUSING	PA-9T	COLOR: BLACK
2	SHELL	SPCC	PLATING: Ni
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni
ITEM	DESC.	MATERIAL	REMAKS

△				QUALITY SYMBOLS	Tolerance	NAME:	SCSI FEMALE V/T SMT(20P,26P,36P) (客户用图)				PART NO.	B03-0XX011EB-02	
△				□:    ☒:	x.    ±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
△	2015/04/09新版发行		King Zhou	CRITICAL    MAJOR	.x    ±0.50	SCALE:	N:1	DATE:	2015/04/09	DAWN HU	KING ZHOU		B03-037
SIDE	DATE	DESCRIPTION	APPROVER	▽:    ▽:	.xx    ±0.25					<b>Lineconn</b> 东莞市林诚塑胶电子有限公司    http://www.lineconn.com TEL:0769-85181660 85181770			
8	7	6	5	4	3	2	1						