



Termination Cover
(1 Places)



Wire Holder
(2 Places)

- Current Rating: 1 Amp
- Insulation Resistance: 500MΩ/Min
- Withstanding Voltage: 500V AC/Min
- Contact Resistance: 35mΩ Max
- Operation Temperature: -25°C ~ +85°C

PART NO: B03-036111E0-X0

WIRE HOLDER: _____
 28AWG or 30AWG WIRE
 6= 0.62mm
 7= 0.75mm
 9= 0.90mm

4	COVER	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK
3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK
2	SHELL	SPCC	PLATING: Ni
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni
ITEM	DESC.	MATERIAL	REMARKS

△			
△			
△	2008/08/20 新版发行	King Zhou	
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS	
□:	☒:
CRITICAL	MAJOR
▽:	▽:
ZERO DEFECT	S.P.C

Tolerance	
.x	±0.80
.x	±0.50
.xx	±0.30

NAME:		SCSI 36P MALE IDC刺破式 ASSEMBLY CONN. (客户用图)		PART NO.	B03-036111E0-X0	
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY
SCALE:	N:1	DATE:	2008/08/20	JACK CHEN	DEAN FAN	DRAWING NO. B03-061
东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL:0769-85181660 85181770		
4	3	2	1			