



• ELECTRICAL CHARACTERISTICS

- Contact Current Rating: 1 Amp
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance: 500MΩ/Min
- Contact Resistance: 35mΩ/Max
- Operation Temperature: -25°C ~ +85°C

4	COVER	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK	
3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

△			
△			
△	2008/08/12 新版发行	King Zhou	

QUALITY SYMBOLS		Tolerance		NAME: SCS1 26P MALE SOLDER ASSEMBLY CONN. (客户用图)		PART NO. B03-026311E0-01	
□:	☒:	.x	±0.80	REV:	A	UNIT:	mm
CRITICAL	MAJOR	.x	±0.50	SCALE:	N:1	DATE:	2008/08/12
▽:	▽:	.xx	±0.30	DRW BY: JACK CHEN		CHK BY: DEAN FAN	APP BY:
ZERO DEFECT	S.P.C			DRAWING NO. B03-054			

SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

		http://www.lineconn.com TEL: 0769-85181660 85181770	
4	3	2	1