

No.of Contact	A	B	C	D	E	F
15	16.9	25.0	30.8	19.0	2.29	7.04
26	25.3	33.3	39.2	27.7	2.29	6.88
44	39.0	47.0	53.0	41.0	2.29	6.88
62	55.4	63.5	69.4	57.3	2.41	7.00

Voltage Current Rating:5 AMP.
 Dielectric Withstanding Voltage:1000V AC
 Insulation Resistance:1000MΩ Min.
 Temperature Range:-25°C to +85°C

PART NO:
 B04-0XX7X1AD-E5

NO.OF CONTACT:
 15 = 15 pos
 26 = 26 pos
 44 = 44 pos
 62 = 62 pos

HOUSING COLOR:
 1 = BLACK
 5 = WHITE
 6 = BLUE


ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
6	SCREW	STEEL	PALTING: Ni	
5	BOARDLOCK	COPPER ALLOY	PALTING: Ni	
4	HOUSING	PBT+30%GF	COLOR: SEE PART NO.	
3	REAR SHELL	SPCC	PALTING: Sn	
2	FRONT SHELL	SPCC	PALTING: Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn UNDER-PLATING: Ni	

QUALITY SYMBOLS

□: ☒:
 CRITICAL MAJOR
 ∇: ∇:
 ZERO DEFECTS.P.C

Tolerance

.x ±0.50
 .x ±0.30
 .xx ±0.25



NAME:		HD. D-SUB MALE 180度后铆6.0鱼叉前锁5.0mm螺母 (客户用图)				PART NO.	B04-0XX7X1AD-E5	
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	
SCALE:	N:1	DATE:	2014/09/02	JINGLI	KING ZHOU		B04-029	

Lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
 TEL: 0769-85181660 85181770

△	2014/09/02	NEW ISSUE	JINGLI
SIDE	DATE	DESCRIPTION	APPROVER