



PCB Lay out

No.of Contact	A	B	C	D	E
15	16.3	25.0	30.8	19.0	2.29
26	24.8	33.3	39.1	27.7	2.29
44	38.3	47.0	53.0	41.0	2.29
62	54.8	63.5	69.3	57.3	2.41

Voltage Current Rating:5 AMP.
 Dielectric Withstanding Voltage:1000V AC
 Insulation Resistance:1000MΩ Min.
 Temperature Range:-25℃ to +85℃

PART NO:
 B04-0XX8X1AD-E5

NO.OF CONTACT:
 15 = 15 pos
 26 = 26 pos
 44 = 44 pos
 62 = 62 pos

HOUSING COLOR:
 1 = BLACK
 5 = WHITE
 6 = BLUE

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
6	SCREW	STEEL	PALTING: Ni	
5	BOARDLOCK	COPPER ALLOY	PALTING: Ni	
4	HOUSING	PBT+30%GF	COLOR: SEE PART NO.	
3	REAR SHELL	SPCC	PALTING: Sn	
2	FRONT SHELL	SPCC	PALTING: Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn UNDER-PLATING: Ni	

△	2014/09/02	NEW ISSUE	JINGLI	QUALITY SYMBOLS	Tolerance
SIDE	DATE	DESCRIPTION	APPROVER	□: ☒:	x. ±0.50
8	7	6	5	CRITICAL MAJOR	.x ±0.30
				▽: ▽:	.xx ±0.25
				ZERO DEFECTS.P.C	

NAME:	HD, D-SUB FEMALE 180度后铆6.0鱼叉 前锁5.0mm螺母 (客户用图)			PART NO.	B04-0XX8X1AD-E5	
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY
SCALE:	N:1	DATE:	2014/09/02	JINGLI	KING ZHOU	DRAWING NO. B04-030
东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL: 0769-85181660 85181770		

8 7 6 5 4 3 2 1

F

E

D

C

B

A

F

E

D

C

B

A

8 7 6 5 4 3 2 1