


High Power Current Rating:10,20 or 40 AMP.
 High Power Current Resistance:2.7 Milliohms MAX.
 Dielectric Withstanding Voltage:1000V AC
 Insulation Resistance:5000MΩ Min.
 Temperature Range:-25°C to +85°C

PART NO: B08-5W54114N-X0

Current Rating: _____
 A = 10 AMPS Dim.A ϕ 1.70
 B = 20 AMPS Dim.A ϕ 2.80
 C = 30 AMPS Dim.A ϕ 3.30
 D = 40 AMPS Dim.A ϕ 4.60



4	REAR SHELL	SPCC	PALTING:Sn	
3	FRONT SHELL	SPCC	PALTING:Ni	
2	HOUSING	PBT+30%GF	COLOR:BLACK	
1	TERMINAL	COPPER ALLOY	TERMINAL FINISH:FULL GOLD FINISHED 2u"	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

QUALITY SYMBOLS

□: ☒: CRITICAL MAJOR
 ▽: ▽: ZERO DEFECT S.P.C

Tolerance

.x ±0.50
 .x ±0.30
 .xx ±0.25

NAME:

5W5母头焊线式光孔POWER D-SUB (客户用图)

REV: A

UNIT: mm

DRW BY: JINGLI

CHK BY: KING ZHOU

PART NO: B08-5W54114N-X0


SCALE: N:1

DATE: 2013/03/16

JINGLI

APP BY:

DRAWING NO: B08-013



lineconn 东莞市林诚塑胶电子有限公司

http://www.lineconn.com
 TEL:0769-85181660 85181770

△	2013/03/16	NEW ISSUE	JINGLI
SIDE	DATE	DESCRIPTION	APPROVER