

High Power Contact Current Rating:
10,20 or 40AMPS
High Power Contact Resistance:
2.7 Milliohms Max.
Dielectric Withstanding Voltage:
1000V AC For 1 Minute
Insulation Resistance:5000MΩ Min.
Temperature Range:-25℃ to +85℃

PART NO:

B08-9W441140-X1

Current Rating:

- A = 10 AMPS Dim.A ø1.70
- B = 20 AMPS Dim.A ø2.80
- C = 30 AMPS Dim.A ø3.20
- D = 40 AMPS Dim.A ø4.60

| 4 | HOUSING | PBT+30%GF | COLOR:BLACK | |
|------|-------------|-----------|--|-------------|
| 3 | REAR SHELL | SPCC | PLATING:Sn | |
| 2 | FRONT SHELL | SPCC | PLATING:Ni | |
| 1 | TERMINAL | BRASS | TERMINAL FINISH:FULL GOLD FINISHED 2u" | |
| ITEM | DESC. | MATERIAL | REMAKS | PART REMAKS |


QUALITY SYMBOLS

□: ☒:
CRITICAL MAJOR
▽: ▽:
ZERO DEFECT S.P.C

Tolerance

x. ±0.50
.x ±0.30
.xx ±0.25

| | | | | | | | |
|--------|-----|-------------------------------|------------|--------|-----------|-----------------|-------------|
| NAME: | | 9W4母头焊线式光孔 POWER D-SUB (客户用图) | | | PART NO. | B08-9W441140-X1 | |
| REV: | A | UNIT: | mm | DRW BY | CHK BY | APP BY | DRAWING NO. |
| SCALE: | N:1 | DATE: | 2012/11/19 | JINGLI | KING ZHOU | | B08-017 |



lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
TEL:0769-85181660 85181770

| △ | 2012/11/19 | NEW ISSUE | JINGLI |
|------|------------|-------------|----------|
| SIDE | DATE | DESCRIPTION | APPROVER |