

PCB LAYOUT

High Power Contact Current Rating:
10,20 or 40AMPS
High Power Contact Resistance:
2.7 Milliohms Max.
Dielectric Withstanding Voltage:
1000V AC For 1 Minute
Insulation Resistance:5000MΩ Min.
Temperature Range:-25°C to +85°C

PART NO:

B08-2W25114D-X1

Current Rating:

- A = 10 AMPS Dim.A ϕ 1.7 Dim.B ϕ 2.2
- B = 20 AMPS Dim.A ϕ 2.8 Dim.B ϕ 3.3
- C = 30 AMPS Dim.A ϕ 3.2 Dim.B ϕ 3.7
- D = 40 AMPS Dim.A ϕ 3.7 Dim.B ϕ 4.2


ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
6	JACKSCREWS	BRASS	PLATING: Ni	
5	HOUSING	PBT+30%GF	COLOR: WHITE	
4	RIVETED INSERT	BRASS	PLATING: Ni	
3	REAR SHELL	SPCC	PLATING: Sn	
2	FRONT SHELL	SPCC	PLATING: Ni	
1	TERMINAL	BRASS	TERMINAL FINISH: FULL GOLD FINISHED 2u"	

QUALITY SYMBOLS

□: ☒: CRITICAL MAJOR
▽: ▽: ZERO DEFECT S.P.C

Tolerance

x. ±0.50
.x ±0.30
.xx ±0.25



NAME:

2W2 90度公头柳支架鱼叉锁螺丝 POWER D-SUB (客户用图)

REV:

A UNIT: mm DRW BY

SCALE:

N:1 DATE: 2012/11/19 JINGLI

PART NO.

B08-2W25114D-X1

CHK BY

APP BY DRAWING NO.

KING ZHOU

B08-001

lineconn

东莞市林诚塑胶电子有限公司

http://www.lineconn.com
TEL:0769-85181660 85181770

SIDE	DATE	DESCRIPTION	APPROVER
△	2012/11/19	NEW ISSUE	JINGLI