



High Power Contact Current Rating:
10,20 or 40AMPS
High Power Contact Resistance:
2.7 Milliohms Max.
Dielectric Withstanding Voltage:
1000V AC For 1 Minute
Insulation Resistance:5000MΩ Min.
Temperature Range:-25°C to +85°C

PART NO:
B08-5W15114D-X1

Current Rating: _____
A = 10 AMPS Dim.A Ø1.7 Dim.B Ø2.2
B = 20 AMPS Dim.A Ø2.8 Dim.B Ø3.3
C = 30 AMPS Dim.A Ø3.2 Dim.B Ø3.7
D = 40 AMPS Dim.A Ø3.7 Dim.B Ø4.2

ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS
6	JACKSCREWS	BRASS	PLATING: Ni	
5	HOUSING	PBT+30%GF	COLOR: WHITE	
4	RIVETED INSERT	BRASS	PLATING: Ni	
3	REAR SHELL	SPCC	PLATING: Sn	
2	FRONT SHELL	SPCC	PLATING: Ni	
1	TERMINAL	BRASS	TERMINAL FINISH: FULL GOLD FINISHED 2u"	

QUALITY SYMBOLS
□: ☒: CRITICAL MAJOR
▽: ▽: ZERO DEFECT S.P.C

Tolerance
.x ±0.50
.x ±0.30
.xx ±0.25

NAME:	5W1 90度公头铆支架鱼叉锁螺丝 POWER D-SUB (客户用图)				PART NO.	B08-5W15114D-X1		
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	
SCALE:	N:1	DATE:	2017/04/29	JINGLI	KING ZHOU		B08-033	

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
TEL:0769-85181660 85181770

△	2017/04/29	NEW ISSUE	JINGLI
SIDE	DATE	DESCRIPTION	APPROVER