

PCB LAYOUT


High Power Contact Current Rating:
10,20 or 40AMPS
High Power Contact Resistance:
2.7 Milliohms Max.
Dielectric Withstanding Voltage:
1000V AC For 1 Minute
Insulation Resistance:5000MΩ Min.
Temperature Range:-25°C to +85°C

PART NO:
B08-3W35114D-X1

Current Rating: _____
A = 10 AMPS Dim.A $\phi 1.7$ Dim.B $\phi 2.2$
B = 20 AMPS Dim.A $\phi 2.8$ Dim.B $\phi 3.3$
C = 30 AMPS Dim.A $\phi 3.2$ Dim.B $\phi 3.7$
D = 40 AMPS Dim.A $\phi 3.7$ Dim.B $\phi 4.2$

6	JACKSCREWS	BRASS	PLATING: Ni	
5	HOUSING	PBT+30%GF	COLOR: WHITE	
4	RIVETED INSERT	BRASS	PLATING: Ni	
3	REAR SHELL	SPCC	PLATING: Sn	
2	FRONT SHELL	SPCC	PLATING: Ni	
1	TERMINAL	BRASS	TERMINAL FINISH: FULL GOLD FINISHED 2u"	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

				QUALITY SYMBOLS	Tolerance	NAME:	3W3 90度公头铆支架鱼叉锁螺丝 POWER D-SUB (客户用图)			PART NO.	B08-3W35114D-X1	
				□: ☒:	x. ±0.50	REV:	A	UNIT:	mm	DRW BY	CHK BY	DRAWING NO.
				CRITICAL MAJOR	.x ±0.30	SCALE:	N:1	DATE:	2017/01/05	JINGLI	KING ZHOU	B08-025
				▽: ▽:	.xx ±0.25							
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C		Lineconn 东莞市林诚塑胶电子有限公司			http://www.lineconn.com			
8	7	6	5	4	TEL:0769-85181660 85181770					1		



Lineconn 东莞市林诚塑胶电子有限公司
http://www.lineconn.com
TEL:0769-85181660 85181770