



Voltage Current Rating: 1 AMP. 30V AC
Dielectric Withstanding Voltage: 500V AC
 Contact Resistance: 35 mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Temperature Range: -20°C to +85°C

PART NO.:

B03-050618X7-01

CONTACT AREA:
 A:G/F
 C:Au 3u"
 H:Au 15u"

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
5	BRACKET	STEEL	PLATING: Ni	
4	COVER	LCP+30%GF	COLOR: BLACK	
3	HOUSING	PBT+30%GF	COLOR: BLACK	
2	SHELL	ZINC ALLOY	PLATING: Ni	
1	TERMINAL	COPPER ALLOY T=0.3mm	CONTACT AREA: SEE NOTE SOLDER AREA: Sn UNDER-PLATING: Ni	

A	△	2021/03/22	修正标注错误尺寸, 修正鱼叉外露尺寸	Jack Chen	QUALITY SYMBOLS □: ☒: CRITICAL MAJOR ▽: ▽: ZERO DEFECT S.P.C	Tolerance .x ±0.80 .x ±0.50 .xx ±0.25	NAME: SCS1 50P FEMALE 90度DIP 锌合金壳 (客户用图)				PART NO.	B03-050618X7-01		
	△	2020/08/10	依实物修正PIN针排列方式	Jack Chen			REV:	C	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
	△	2015/05/12	新版发行	Jack Chen			SCALE:	N:1	DATE:	2015/05/12	Jing Li	Jack Chen		B03-005
	SIDE	DATE	DESCRIPTION				APPROVER	东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL: 0769-85181660 85181770		
	8	7	6	5	4	3	2	1						