



ELECTRICAL:

- Current Rating: 1 Amp
- Insulation Resistance: 500MΩ/Min
- Withstanding Voltage: 250V AC/Min
- Contact Resistance: 35mΩ Max
- Temperature Range: -25°C ~ +85°C

3	HOUSING	LCP+30%GF	COLOR:BEIGE	
2	SHELL	SPCC	PLATING:Ni	
1	TERMINAL	COPPER ALLOY T=0.3mm	CONTACT AREA:G/F SOLDER AREA:Sn UNDER-PLATING:Ni	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

				QUALITY SYMBOLS	Tolerance	NAME:	CISCO 26P PITCH 1.0mm MALE SOLDER TYPE (客户用图)				PART NO.	B06-0263C1AN-02		
△	2021/04/14	修正电气参数	JACK CHEN	□: ☒:	x. ±0.50	REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	
△	2014/09/23	NEW ISSUE	JACK CHEN	CRITICAL MAJOR	.x ±0.30	SCALE:	N:1	DATE:	2014/09/23	JACK CHEN	KING ZHOU		B06-012	
SIDE	DATE	DESCRIPTION	APPROVER	▽: ▽:	.xx ±0.25	 东莞市林诚塑胶电子有限公司							http://www.lineconn.com TEL:0769-85181660 85181770	

				QUALITY SYMBOLS	Tolerance	NAME:	CISCO 26P PITCH 1.0mm MALE SOLDER TYPE (客户用图)				PART NO.	B06-0263C1AN-02		
△	2021/04/14	修正电气参数	JACK CHEN	□: ☒:	x. ±0.50	REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	
△	2014/09/23	NEW ISSUE	JACK CHEN	CRITICAL MAJOR	.x ±0.30	SCALE:	N:1	DATE:	2014/09/23	JACK CHEN	KING ZHOU		B06-012	
SIDE	DATE	DESCRIPTION	APPROVER	▽: ▽:	.xx ±0.25	 东莞市林诚塑胶电子有限公司							http://www.lineconn.com TEL:0769-85181660 85181770	