



No. of Contact	A	B	C	D
15	16.9	25.0	30.8	19.3
26	25.2	33.3	39.1	27.5
44	39.0	47.0	53.0	41.3
62	55.4	63.5	69.3	57.7

Voltage Current Rating:5 AMP.
 Dielectric Withstanding Voltage:1000V AC
 Insulation Resistance:1000MΩ Min.
 Temperature Range:-25°C to +85°C

PART NO: B04-0XX3X1AN-01

NO.OF CONTACT:
 15 = 15 pos
 26 = 26 pos
 44 = 44 pos
 62 = 62 pos

HOUSING COLOR:
 1 = BLACK
 5 = WHITE
 6 = BLUE

4	REAR SHELL	SPCC	PALTING: Sn
3	FRONT SHELL	SPCC	PALTING: Ni
2	HOUSING	PBT+30%GF	COLOR: SEE PART NO.
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn
ITEM	DESC.	MATERIAL	REMAKS

QUALITY SYMBOLS		Tolerance		NAME: HD.D-SUB 传统公头焊线式通孔 (客户用图)				PART NO. B04-0XX3X1AN-01			
□:	☒:	x.	±0.50	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
CRITICAL	MAJOR	.x	±0.30	SCALE:	N:1	DATE:	2009/04/14	JINGLI	KING ZHOU		B04-002
▽:	▽:	.xx	±0.25	东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL:0769-85181660 85181770			
ZERO DEFECT	S.P.C										

SIDE	DATE	DESCRIPTION	APPROVER
△	2009/04/14	NEW ISSUE	JINGLI