



PART NO.:
B03-0363X1X2-X1

COLOR:
1:BLACK
C:BEIGE

CONTACT AREA:
A:G/F
E:Au 5u"
H:Au 15u"

HOOD OD DIM"A":
A:6.7mm
B:7.7mm
C:8.7mm

ELECTRICAL CHARACTERISTICS

Contact Current Rating: 1 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 500MΩ/Min
 Contact Resistance: 35mΩ/Max
 Operation Temperature: -25°C ~ +85°C

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
6	SHRAPNEL	SUS		
5	OUTSIDE SHEEL	SPCC (t=0.50mm)	PLATING:Ni	
4	HOOD&WRENCH	ABS+G.F.30% (UL 94V-0)	COLOR:SEE P/N	
3	HOUSING&COVER	PBT+G.F.30% (UL 94V-0)	COLOR:BLACK	
2	SHEEL	SPCC (t=0.50mm)	PLATING:Ni	
1	TERMINAL	COPPER ALLOY (t=0.25mm)	CONTACT AREA:P/N SOLDER AREA:Sn UNDER-PLATING:	

△				QUALITY SYMBOLS
△				□: ⊠:
△	2019/10/08	NEW ISSUE	Jack Chen	CRITICAL MAJOR
SIDE	DATE	DESCRIPTION	APPROVER	▽: ▽:
8	7			ZERO DEFECT S.P.C

Tolerance		NAME: SCSI 36P MALE 焊线塑壳装配式鱼钩弹片 (客户用图)				PART NO. B03-0363X1X2-X1	
x.	±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY
.x	±0.50	SCALE:	N:1	DATE:	2019/10/08	Huangmei	Jack Chen
.xx	±0.30	东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL:0769-85181660 85181770	