



RoHS



PIN ASSIGNMENT

NOTES:

1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
2. CONDUCTOR RESISTANCE: 5 OHMS MAX.
3. INSULATOR RESISTANCE: 1M OHMS MIN, DC 300V 0.01sec.
4. THIS PRODUCT MEET ROHS STANDARD ENVIRONMENTAL PROTECTION POLICY.

7	SCREW	SCREW 4-40# Ni(大 E33 BLACK)	4PCS
6	CABLE	UL2919 28AWG*7P+28AWG*1C+AEB PVC JACKET COLOR:BLACK OD= 7.5mm	1PCS
5	COPPER FOL	COPPER FOIL W=25MM	NA
4	OVERMOLD	45P PVC COLOR: BLACK	NA
3	MOLD	PE	NA
2	CONNECTOR	HD-SUB 15Pin Female Solder BLACK TYPE	1PCS
1	CONNECTOR	HD-SUB 15Pin Male Solder BLACK TYPE	1PCS
ITEM	PART NAME	DESCRIPTION	QY'T

A	△			QUALITY SYMBOLS	Tolerance		NAME:	HD-D-SUB 15P Male To 15P Female Cable (客户用图)		PART NO.	A04-01531XXX-01			
	△			□: ☒:	尺寸(CM)	公差(CM)	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
	△	2018/04/07	新版发行	CRITICAL MAJOR	201~500	±20	SCALE:	NONE	DATE:	2018/04/07	Jack Chen	Hua Guan		A04-003
	△			▽: ▽:	501~	±30	lineconn 东莞市林诚塑胶电子有限公司		http://www.lineconn.com		TEL:0769-85181660 85181770			
	SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT	S.P.C								
	8	7	6	5	4		3	2	1					