



• ELECTRICAL CHARACTERISTICS

Contact Current Rating: 1 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 500MΩ/Min
 Contact Resistance: 35mΩ/Max
 Operation Temperature: -25°C ~ +85°C

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
5	LATCH	SUS 304		
4	HOOD	PC+ABS	COLOR: GRAY	
3	HOUSING	LCP+30%GF	COLOR: BLACK	
2	SHELL	SPCC	PLATING: NI	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn UNDER-PLATING: Ni	

SIDE	DATE	DESCRIPTION	APPROVER	QUALITY SYMBOLS	Tolerance	NAME:	PART NO.	CHK BY	APP BY	DRAWING NO.
△				□: ☒:	x. ±0.80	SM 6P MALE SOLDER伺服连接器 B模 (客户用图)	B01-006321A1-02			
△				CRITICAL MAJOR	.x ±0.50	REV: A UNIT: mm DRW BY				B01-019
△	2021/04/23	新版发行	King Zhou	▽: ▽:	.xx ±0.30	SCALE: N:1 DATE: 2021/04/23 Shuo Cao	Jack Chen			
				ZERO DEFECT S.P.C		lineconn 东莞市林诚塑胶电子有限公司	http://www.lineconn.com TEL:0769-85181660 85181770			