



P.C.B LAYOUT

No. of Contact	3		2		1		
	A	B	C	D	E	F	G
15	16.3	25.0	30.8	19.3	2.29	7.04	0.25
26	24.6	33.3	39.1	27.5	2.29	6.88	0.51
44	36.3	47.0	53.0	41.3	2.29	6.88	0.51
62	54.8	63.5	69.3	57.7	2.41	7.00	0.58

Voltage Current Rating:5 AMP.
 Dielectric Withstanding Voltage:1000V AC
 Insulation Resistance:5000MΩ Min.
 Temperature Range:-25°C to +85°C

PART NO: B04-0XX6X14D-02

NO.OF CONTACT:
 15 = 15 pos
 26 = 26 pos
 44 = 44 pos
 62 = 62 pos

HOUSING COLOR:
 1 = BLACK
 5 = WHITE
 6 = BLUE

No. of Contact	No.A	No.B	No.C	No.D	No.E
15	Pin 5	Pin 6	Pin 10	Pin 11	Pin 15
26	Pin 9	Pin 10	Pin 18	Pin 19	Pin 26
44	Pin 15	Pin 16	Pin 30	Pin 31	Pin 44
62	Pin 21	Pin 22	Pin 42	Pin 43	Pin 62

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
5	SCREW	STEEL	PALTING: Ni	
4	BOARDLOCK	COPPER ALLOY	PALTING: Ni	
3	HOUSING	PBT+30%GF	COLOR: BLACK	
2	SHELL	SPCC	PALTING: Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: Au 2u" SOLDER AREA: Au 2u" UNDER-PLATING: Ni	

SIDE	DATE	DESCRIPTION	APPROVER
△	2022/12/01	增加尺寸标注	Jack Chen
△	2011/06/14	NEW ISSUE	JINGLI

QUALITY SYMBOLS		Tolerance	
□:	☒:	.x	±0.50
CRITICAL	MAJOR	.x	±0.30
▽:	▽:	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:	HD. D-SUB 车针母头90度插板8.89mm折弯挡板支架鱼叉锁螺丝 (客户用图)			PART NO.	B04-0XX6X14D-02		
REV:	B	UNIT:	mm	DRW BY	Huangmei	CHK BY	Jack Chen
SCALE:	N:1	DATE:	2011/06/14	APP BY		DRAWING NO.	
东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL:0769-85181660 85181770			