



• ELECTRICAL CHARACTERISTICS

Contact Current Rating: 1 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 500MΩ/Min
 Contact Resistance: 35mΩ/Max
 Operation Temperature: -25°C ~ +85°C

ITEM	DESC.	MATERIAL	REMARKS
6	SCREW	STAINLESS STEEL	PLANTING: Ni
5	TERMINAL	COPPER ALLOY	CONTACT FINISH OVER-PLATING: Au 3u" SOLDER FINISH OVER-PLATING: G/F
4	WRENCH SPRING	STAINLESS STEEL	PLANTING: Ni
3	SHELL	SPCC (T=0.50mm)	PLANTING: Ni
2	COVER	ABS	COLOR: BLACK
1	HOUSING	PBT+30%G.F.,UL94V-0	COLOR: BLACK

△				QUALITY SYMBOLS	Tolerance	NAME:	SM 10P MALE SOLDER 伺服连接器 (客户用图)				PART NO.	B01-01031131-01	
△				□: ☒:	x. ±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
△	2016/07/14	新开模新版发行	King Zhou	CRITICAL MAJOR	.x ±0.50	SCALE:	N:1	DATE:	2016/07/14	Huangmei	Jack Chen		B01-008
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C	.xx ±0.30	lineconn 东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL:0769-85181660 85181770			
8	7	6	5	4	3	2	1						

△				QUALITY SYMBOLS	Tolerance	NAME:	SM 10P MALE SOLDER 伺服连接器 (客户用图)				PART NO.	B01-01031131-01	
△				□: ☒:	x. ±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
△	2016/07/14	新开模新版发行	King Zhou	CRITICAL MAJOR	.x ±0.50	SCALE:	N:1	DATE:	2016/07/14	Huangmei	Jack Chen		B01-008
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C	.xx ±0.30	lineconn 东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL:0769-85181660 85181770			
8	7	6	5	4	3	2	1						