



Voltage Current Rating: 5 AMP.
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 1000MΩ Min.
 Temperature Range: -25°C to +85°C

PART NO: B17-0XX3X1AF-02
 CONTACT NO.:
 14: 14PIN
 24: 24PIN
 36: 36PIN
 50: 50PIN
 HOUSING COLOR:
 1:BLACK
 6:BLUE

Positions	A±0.3	B±0.35	C±0.35	D±0.25	E±0.25	F± ^{+0.2} _{-0.4}
14	25.3	37.9	15.8	7.0	17.45	25.44
24	36.0	49.0	15.8	9.0	28.35	36.24
36	49.3	61.6	15.8	11.5	41.35	49.2
50	64.2	77.1	16	12.5	56.35	64.32

3	HOUSING	PBT+30%G.F.(UL 94V-0)	COLOR:SEE PART NO.	
2	SHELL	SPCC	OVER-PLATING: Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA:G/F SOLDER AREA:Sn UNDER-PLATING:Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

A		B		C		D		E		F	
△	2022/07/05	变更料号		JINGLI		QUALITY SYMBOLS		Tolerance		NAME: 57-传统公焊线式+30大铁壳 (客户用图)	
△	2012/07/12	NEW ISSUE		JINGLI		CRITICAL MAJOR		x. ±0.50		REV: B UNIT: mm DRW BY CHK BY APP BY DRAWING NO.	
△	2012/07/12	NEW ISSUE		JINGLI		MAJOR		.x ±0.30		SCALE: N:1 DATE: 2012/07/12 JINGLI KING ZHOU	
△	2012/07/12	NEW ISSUE		JINGLI		S.P.C		.xx ±0.25		http://www.lineconn.com	
SIDE	DATE	DESCRIPTION		APPROVER		ZERO DEFECT S.P.C				Lineconn 东莞市林诚塑胶电子有限公司 TEL:0769-85181660 85181770	